


1/10

FIG. 1



20020304 180000

2/10

FIG. 2(A)






FIG. 2(B)




3/10

FIG. 3



4/10


FIG. 4
30 WOBBLED INTERMITTENT
DETECTION CIRCUIT




5/10

FIG. 5

(A) PUSH-PULL SIGNAL



(B) OUTPUT OF COMPARATOR 31



(C) OUTPUT OF COMPARATOR 32



(D) REFERENCE SIGNAL



(E) DETECTION SIGNAL




6/10

FIG. 6

(A) LOGIC "0"

PUSH-PULL SIGNAL




DETECTION SIGNAL

REFERENCE POSITION
SIGNALPREDETERMINED
REGION

ONE SET

(B) LOGIC "1"

PUSH-PULL SIGNAL



DETECTION SIGNAL

REFERENCE POSITION
SIGNALPREDETERMINED
REGION

ONE SET

7/10

FIG. 7(A)





FIG. 7(B)




8/10

FIG. 8

(A) **LOGIC "0"**

PUSH-PULL SIGNAL




DETECTION SIGNAL

REFERENCE POSITION
SIGNAL

ONE SET

(B) **LOGIC "1"**

PUSH-PULL SIGNAL





DETECTION SIGNAL

REFERENCE POSITION
SIGNAL

ONE SET

2002年 3月 4日 18時01分


9/10



10/10

FIG. 10(A) **LOGIC "0"**

PUSH-PULL SIGNAL




DETECTION SIGNAL

REFERENCE POSITION
SIGNAL

ONE SET

(B) **LOGIC "1"**

PUSH-PULL SIGNAL



DETECTION SIGNAL

REFERENCE POSITION
SIGNAL

ONE SET